



Angle Grinders

Longtime best selling NPK angle grinders for various industrial applications.



Non Governor

100mm(4") / Grip 125mm(5") / Grip



NAG-1F-04



NAG-1F-05

100mm(4") / Safety Grip 125mm(5") / Safety Grip



NAG-1FLW-04



NAG-1FLW-05

Wheel not included.

Model	Code	Wheel size		Spindle thread	Max.free speed	Overall length		Height		Weight		Max. output		Air inlet thread	Hose size		Average air consumption	
		mm	in			in	mm	in	mm	in	kg	lb	kw		hp	Rc	mm	in
NAG-1F-04	15324	100x6x15.9	4x ¹ / ₄ x ⁵ / ₈	-	12700	190	7 ¹ / ₂	83	3 ¹ / ₄	1.5	3.3	0.87	1.19	1/4	9.5	3/8	0.68	24
NAG-1FLW-04	15319	100x6x15.9	4x ¹ / ₄ x ⁵ / ₈	-	12700	232	9 ¹ / ₈	79	3 ¹ / ₈	1.5	3.3	0.87	1.19	1/4	9.5	3/8	0.68	24
NAG-1F-05	15331	125x6x22.2	5x ¹ / ₄ x ⁷ / ₈	-	12000	187	7 ³ / ₈	77	3 ¹ / ₁₆	1.6	3.5	0.87	1.19	1/4	9.5	3/8	0.68	24
NAG-1FLW-05	15326	125x6x22.2	5x ¹ / ₄ x ⁷ / ₈	-	12000	232	9 ¹ / ₈	83	3 ¹ / ₄	1.6	3.5	0.87	1.19	1/4	9.5	3/8	0.68	24

Built-in Governor

100mm(4") / Grip 100mm(4") / Safety Grip



NAG-400A-EX



Optional left handle.

NGS-100



Compact & Lightweight



- Quick wheel change with spindle lock.

100mm(4") / Safety Grip 125mm(5") / Safety Grip

NGP-100



Heavy-duty



- Quick wheel change with spindle lock.

NGP-125



Heavy-duty



- Quick wheel change with spindle lock.

Wheel not included.

Model	Code	Wheel size		Spindle thread	Max.free speed	Overall length		Height		Weight		Max. output		Air inlet thread	Hose size		Average air consumption	
		mm	in			in	mm	in	mm	in	kg	lb	kw		hp	Rc	mm	in
NAG-400A-EX	70661	100x6x15.9	4x ¹ / ₄ x ⁵ / ₈	-	13600	216	8 ¹ / ₂	86	3 ³ / ₈	1.7	3.7	0.85	1.15	1/4	9.5	3/8	0.65	23
NGS-100	15208	100x6x15	4 x ¹ / ₄ x ⁹ / ₁₆	-	13600	192	7 ⁹ / ₁₆	85	3 ³ / ₈	1.0	2.2	0.64	0.88	1/4	9.5	3/8	0.5	17.7
NGP-100	15239	100x6x15	4x ¹ / ₄ x ⁹ / ₁₆	-	13600	225	7 ⁷ / ₈	97	3 ¹³ / ₁₆	1.8	3.7	1.2	1.63	3/8	9.5	3/8	1.0	35.3
NGP-125	15318	125x6x22	5x ¹ / ₄ x ⁷ / ₈	-	10900	225	7 ⁷ / ₈	105	4 ¹ / ₈	1.9	4.2	1.2	1.63	3/8	9.5	3/8	1.0	35.3



Angle Grinders

Longtime best selling NPK angle grinders for various industrial applications.



Built-in Governor

100mm(4") / Safety Lever



NAG-11A-04

125mm(5") / Safety Lever



NAG-11A-05

* 5/8-11 UNC thread spindle is also available.

Features for NAG-11A-04, -05



- Quick wheel change with spindle lock.



- Rear exhaust.



- Right / left replaceable handle.

Model	Code	Wheel size		Spindle thread	Max.free speed	Overall length		Height		Weight		Max. output		Air inlet thread	Hose size		Average air consumption	
		mm	in			mm	in	mm	in	kg	lb	kw	hp		Rc	mm	in	m ³ /min
NAG-11A-04	10794	100x6x15.9	4 x 1/4 x 5/8	-	12000	248	9 3/4	94	3 11/16	2.2	4.8	0.88	1.20	3/8	9.5	3/8	0.8	28.3
NAG-11A-05	10808	125x6x22	5 x 1/4 x 7/8	M14 x2.0	12000	248	9 3/4	98	3 7/8	2.3	5.1	0.88	1.20	3/8	9.5	3/8	0.8	28.3

Non Governor

100mm(4") / Safety Lever



NAG-1FLW-04-CE

- Left side handle included.
- Wheel not included.

125mm(5") / Safety Lever



NAG-1FLW-05-CE

- Left side handle included.
- Wheel not included.

Model	Code	Wheel size		Spindle thread	Max.free speed	Overall length		Height		Weight		Max. output		Air inlet thread	Hose size		Average air consumption	
		mm	in			mm	in	mm	in	kg	lb	kw	hp		Rc	mm	in	m ³ /min
NAG-1FLW-04-CE	15418	100x6x15.9	4 x 1/4 x 5/8	-	12700	232	9 1/8	79	3 1/8	1.5	3.3	0.87	1.19	1/4	9.5	3/8	0.68	24
NAG-1FLW-05-CE	15402	125x6x22.2	5 x 1/4 x 7/8	-	12000	232	9 1/8	83	3 1/4	1.6	3.5	0.87	1.19	1/4	9.5	3/8	0.68	24